

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
3.276	2.148	20	.070/1.78	512542
3.510	2.716	24	.061/1.55	512294
3.700	2.600	33	.115/2.92	512950
3.767	2.619	22	.062/1.57	512787
3.785	3.180	40	.066/1.68	512835
3.855	2.800	36	.062/1.57	512780
3.875	2.635	12	.098/2.49	512807
3.875	2.635	12	.099/2.51	512809
3.875	2.655	12	.063/1.60	512819
3.931	2.689	34	.062/1.57	512881
3.950	2.950	20	.062/1.57	512191
3.997	2.944	30	.068/1.73	512104
4.015	3.115	24	.069/1.75	512667
4.045	3.316	30	.057/1.45	512207
4.057	2.619	22	.062/1.57	512786
4.089	3.190	20	.062/1.57	512741
4.089	3.190	20	.079/2.01	512742
4.166	2.874	38	.076/1.93	512333
4.185	3.305	22	.082/2.08	512928
4.232	2.935	36	.082/2.08	512934
4.240	3.170	39	.099/2.51	512925
4.240	3.055	8	.099/2.51	512940
4.245	3.387	32	.065/1.65	512673
4.246	2.797	36	.062/1.57	512887
4.248	3.462	30	.057/1.45	512208
4.250	2.903	36	.062/1.57	512683
4.250	2.903	36	.062/1.57	512783
4.255	2.551	26	.067/1.70	512968
4.255	3.365	34	.074/1.88	512969
4.255	2.551	26	.067/1.70	512977
4.262	3.352	34	.059/1.50	512813
4.262	3.352	34	.068/1.73	512817
4.262	3.352	34	.068/1.73	512820
4.316	3.742	38	.060/1.52	512291
4.330	3.470	22	.062/1.57	512840
4.330	3.470	22	.062/1.57	512845
4.334	3.386	24	.062/1.57	512139
4.342	3.743	36	.063/1.60	512292
4.365	3.111	24	.062/1.57	512676
4.370	3.210	40	.072/1.83	512908
4.399	3.126	32	.079/2.01	512438
4.399	3.126	32	.095/2.41	512442
4.399	3.126	32	.084/2.13	512446
4.399	3.126	32	.083/2.11	512451
4.410	3.340	24	.062/1.57	512757
4.410	3.340	24	.059/1.50	512776
4.414	3.568	30	.073/1.85	512525
4.415	3.368	21	.062/1.57	512751
4.415	3.420	20	.062/1.57	512755

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
4.435	2.770	28	.072/1.83	512917
4.460	3.329	29	.059/1.50	512594
4.480	3.355	34	.067/1.70	512712
4.480	3.355	34	.067/1.70	512714
4.490	3.255	36	.060/1.52	512473
4.490	3.150	24	.063/1.60	512689
4.490	3.150	24	.078/1.98	512691
4.490	3.150	24	.085/2.16	512694
4.490	3.360	40	.072/1.83	512916
4.500	3.733	30	.059/1.50	512196
4.502	3.360	36	.072/1.83	512991
4.525	3.630	32	.069/1.75	512401
4.525	3.115	24	.062/1.57	512680
4.525	3.675	24	.062/1.57	512681
4.525	3.628	16	.062/1.57	512841
4.525	3.628	16	.062/1.57	512846
4.525	3.389	44	.062/1.57	512959
4.528	3.460	32	.099/2.51	512370
4.528	3.460	32	.063/1.60	512385
4.528	3.480	8 EXT.	.128/3.25	512471
4.528	3.480	8 EXT.	.059/1.50	512472
4.528	3.362	43	.062/1.57	512816
4.528	3.362	43	.093/2.36	512903
4.563	3.433	42	.077/1.96	512336
4.563	3.433	42	.062/1.57	512357
4.563	3.433	42	.077/1.96	512436
4.563	3.433	42	.062/1.57	512688
4.563	3.433	42	.061/1.55	R600320
4.563	3.433	42	.077/1.96	R600325
4.595	3.378	41	.080/2.03	512685
4.600	3.860	18	.062/1.57	512745
4.600	3.685	32	.072/1.83	512905
4.620	3.736	30	.075/1.91	512514
4.631	2.770	28	.073/1.85	512912
4.640	3.310	29	.072/1.83	512064
4.640	3.820	50	.062/1.57	512850
4.645	3.517	24	.062/1.57	512682
4.646	3.280	30	.064/1.63	512429
4.646	3.264	32	.062/1.57	512437
4.646	3.264	32	.090/2.29	512449
4.646	3.264	32	.080/2.03	512500
4.646	3.264	32	.070/1.78	512517
4.647	3.940	50	.068/1.73	512784
4.647	3.881	24	.077/1.96	512954
4.647	3.881	24	.070/1.78	512955
4.650	3.050	20	.062/1.57	512798
4.653	3.430	42	.072/1.83	512223
4.653	3.430	42	.058/1.47	512228
4.653	3.430	42	.067/1.70	R600480

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
4.653	3.430	42	.058/1.47	R600485
4.655	3.599	72	.077/1.96	512371
4.655	3.599	72	.077/1.96	512374
4.655	3.599	72	.069/1.75	512378
4.655	3.599	72	.067/1.70	512381
4.680	3.708	36	.075/1.91	512518
4.680	3.210	40	.086/2.18	512935
4.685	3.431	42	.065/1.65	512243
4.695	3.180	8	.110/2.79	512923
4.704	3.076	36	.076/1.93	512304
4.704	2.986	40	.076/1.93	512334
4.705	3.230	30	.076/1.93	512301
4.708	3.936	30	.058/1.47	512197
4.708	3.939	30	.074/1.88	512201
4.710	3.560	36	.062/1.57	512190
4.764	3.347	30	.077/1.96	512242
4.764	3.844	49	.062/1.57	512831
4.764	3.844	49	.089/2.26	512832
4.765	3.740	32	.100/2.54	512369
4.770	3.690	24	.062/1.57	512338
4.770	3.532	31	.070/1.78	512593
4.796	3.865	24	.062/1.57	512788
4.796	3.865	24	.062/1.57	512791
4.800	3.200	30	.070/1.78	512088
4.802	3.585	30	.062/1.57	512687
4.803	3.317	30	.071/1.80	512109
4.804	3.568	24	.064/1.63	512269
4.805	3.465	24	.078/1.98	512690
4.810	4.047	36	.059/1.50	512132
4.840	4.055	21	.080/2.03	512973
4.843	3.530	36	.065/1.65	512111
4.843	3.563	24	.065/1.65	512235
4.843	3.563	24	.065/1.65	512236
4.845	3.172	24	.086/2.18	512932
4.850	3.890	40	.072/1.83	512077
4.850	3.815	24	.063/1.60	512554
4.853	3.632	30	.059/1.50	512595
4.860	3.856	35	.059/1.50	512210
4.860	3.825	48	.080/2.03	512387
4.879	3.614	30	.063/1.60	512259
4.880	4.117	42	.058/1.47	512211
4.881	3.297	44	.076/1.93	512349
4.882	3.234	8	.062/1.57	512801
4.890	3.839	47	.072/1.83	512403
4.890	3.839	47	.085/2.16	512404
4.890	4.011	49	.072/1.83	512410
4.890	4.011	49	.072/1.83	512411
4.892	3.825	48	.080/2.03	512237
4.892	3.825	48	.077/1.96	512372

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
4.892	3.825	32/48	.077/1.96	512373
4.892	3.825	48	.077/1.96	512375
4.892	3.825	32/48	.077/1.96	512376
4.892	3.825	48	.068/1.73	512377
4.892	3.825	32/48	.069/1.75	512379
4.892	3.825	48	.069/1.75	512380
4.892	3.829	16	.069/1.75	512382
4.892	3.825	48	.080/2.03	R600950
4.892	3.829	16	.067/1.70	R600960
4.915	3.485	30	.062/1.57	512759
4.915	3.485	30	.062/1.57	R600845
4.920	3.695	40	.073/1.85	512911
4.935	4.200	20	.062/1.57	512754
4.940	3.672	45	.085/2.16	512528
4.940	3.672	45	.085/2.16	512529
4.940	3.672	45	.062/1.57	512677
4.940	3.672	45	.062/1.57	512678
4.948	3.861	36	.076/1.93	512331
4.960	4.210	24	.062/1.57	512193
4.960	4.260	30	.072/1.83	512740
4.960	3.963	40	.070/1.78	512924
4.960	3.969	40	.075/1.91	512964
4.960	3.964	40	.072/1.83	512966
4.960	3.964	40	.067/1.70	512967
4.960	3.969	40	.062/1.57	512996
4.961	3.874	44	.073/1.85	512818
4.961	3.874	44	.068/1.73	512824
4.961	3.874	44	.073/1.85	512825
4.973	3.961	32/40	.079/2.01	512984
4.976	4.115	42	.062/1.57	512842
4.976	4.115	42	.062/1.57	512847
4.976	3.965	40	.067/1.70	512980
4.976	3.965	40	.080/2.03	512988
4.976	3.965	40	.078/1.98	512989
4.976	3.965	40	.075/1.91	512995
4.976	3.965	40	.067/1.70	512998
4.977	3.791	46	.080/2.03	512684
4.977	3.791	46	.080/2.03	512686
4.985	3.844	49	.089/2.26	512833
4.989	3.370	12	.079/2.01	512439
4.989	3.370	12	.084/2.13	512447
4.989	3.370	12	.078/1.98	512452
4.990	3.783	24/48	.079/2.01	512869
4.990	3.783	24/48	.093/2.36	512870
4.990	3.717	16	.093/2.36	512871
4.990	3.756	46	.082/2.08	512945
4.990	3.756	46	.071/1.80	512947
4.990	3.815	47	.083/2.11	512949
5.000	3.763	38	.077/1.96	512075

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
5.000	3.750	10	.077/1.96	512078
5.000	3.900	38	.075/1.91	512079
5.000	3.900	38	.067/1.70	512110
5.000	3.873	30	.070/1.78	512540
5.019	4.248	36	.059/1.50	512133
5.020	3.297	30	.076/1.93	512303
5.030	3.132	42	.076/1.93	512342
5.030	3.201	32	.076/1.93	512353
5.030	3.520	36	.080/2.03	512652
5.030	3.520	36	.080/2.03	512702
5.030	3.520	36	.080/2.03	R600270
5.038	3.968	36	.062/1.57	512162
5.039	4.134	30	.075/1.91	512716
5.039	4.134	30	.066/1.68	512717
5.039	4.028	40	.062/1.57	512883
5.042	4.136	30	.077/1.96	512719
5.042	4.136	30	.077/1.96	512723
5.042	4.136	30	.062/1.57	512725
5.042	4.178	8	.062/1.57	512862
5.042	4.178	8	.071/1.80	512863
5.055	4.000	20	.080/2.03	512388
5.059	3.713	30	.077/1.96	512261
5.060	3.653	45	.099/2.51	512433
5.060	3.653	45	.099/2.51	512434
5.060	3.653	45	.099/2.51	512522
5.060	3.653	45	.060/1.52	R600000
5.065	3.235	36	.099/2.51	512642
5.065	3.235	36	.071/1.80	512649
5.089	3.892	30	.064/1.63	512274
5.094	4.093	32/40	.067/1.70	512983
5.099	3.752	40	.080/2.03	512573
5.099	3.749	40	.087/2.21	512804
5.099	3.752	40	.080/2.03	R600060
5.102	4.012	36	.062/1.57	512186
5.102	4.012	36	.062/1.57	R600905
5.110	3.925	40	.072/1.83	512909
5.112	3.937	24	.062/1.57	512180
5.115	3.815	24	.063/1.60	512556
5.115	4.215	24	.063/1.60	512561
5.118	3.572	38	.062/1.57	512444
5.118	3.572	38	.069/1.75	512445
5.118	3.572	38	.069/1.75	512455
5.120	4.205	45/54	.096/2.44	512951
5.120	3.990	51	.094/2.39	512957
5.120	3.990	51	.077/1.96	512958
5.120	3.990	51	.078/1.98	512960
5.137	4.336	18	.079/2.01	512743
5.151	3.990	30	.064/1.63	512171
5.151	3.990	30	.077/1.96	512418

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
5.160	4.125	12	.063/1.60	512555
5.160	4.150	44	.062/1.57	512849
5.160	4.150	44	.062/1.57	512851
5.160	4.165	44	.062/1.57	512855
5.165	4.450	36	.066/1.68	512836
5.165	4.450	36	.066/1.68	512839
5.179	3.961	32/40	.080/2.03	512982
5.179	3.961	40	.080/2.03	512990
5.179	3.961	32/40	.080/2.03	512999
5.180	3.964	40	.078/1.98	512195
5.180	3.964	40	.080/2.03	512981
5.180	3.961	40	.080/2.03	512997
5.185	3.960	40	.067/1.70	512937
5.192	3.710	49	.076/1.93	512346
5.205	4.135	36	.076/1.93	512330
5.207	4.557	36	.061/1.55	512293
5.218	4.050	30	.098/2.49	512805
5.218	4.050	30	.098/2.49	512810
5.218	4.050	30	.098/2.49	R600900
5.220	4.215	30	.062/1.57	512158
5.224	3.365	45	.076/1.93	512343
5.224	3.262	42/44	.076/1.93	512344
5.224	3.417	32	.076/1.93	512354
5.225	4.065	30	.080/2.03	512570
5.225	4.015	30	.063/1.60	512728
5.225	4.065	30	.061/1.55	R600030
5.225	4.065	30	.080/2.03	R600035
5.228	4.472	89	.068/1.73	512383
5.228	4.472	89	.067/1.70	R600955
5.234	4.140	30	.062/1.57	512726
5.242	4.369	22	.099/2.51	512942
5.250	3.653	45	.062/1.57	512178
5.250	3.653	45	.062/1.57	512226
5.250	3.653	45	.077/1.96	512227
5.250	3.653	45	.077/1.96	512320
5.250	3.653	45	.059/1.50	512321
5.250	4.412	18	.078/1.98	512730
5.250	4.412	18	.078/1.98	512735
5.250	3.653	45	.063/1.60	R600470
5.255	3.875	42/44	.072/1.83	512054
5.265	4.338	30	.082/2.08	512120
5.270	3.803	24	.086/2.18	512931
5.276	4.038	32	.065/1.65	512230
5.276	3.850	24	.065/1.65	512231
5.276	3.850	24	.065/1.65	512232
5.300	4.490	30	.077/1.96	512856
5.300	4.490	30	.062/1.57	512888
5.305	3.925	36	.070/1.78	512544
5.307	3.703	48	.070/1.78	512543

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
5.310	3.260	32	.062/1.57	512430
5.310	3.260	32	.070/1.78	512456
5.310	3.815	24	.063/1.60	512558
5.310	3.740	51	.086/2.18	512929
5.310	3.740	51	.097/2.46	512930
5.313	4.012	41	.080/2.03	512650
5.313	4.012	41	.069/1.75	512653
5.313	4.012	41	.080/2.03	512700
5.313	4.012	41	.069/1.75	512704
5.313	4.012	41	.070/1.78	512708
5.313	4.012	41	.069/1.75	R600240
5.315	2.963	18	.070/1.78	512440
5.315	2.964	18	.070/1.78	512443
5.315	2.964	18	.090/2.29	512448
5.328	3.731	51	.099/2.51	512094
5.328	3.653	34	.076/1.93	512302
5.335	3.836	24	.091/2.31	512494
5.345	4.482	48/57	.095/2.41	512953
5.345	4.482	48/57	.090/2.29	512956
5.360	4.380	30	.067/1.70	512102
5.360	3.656	45	.062/1.57	512229
5.370	4.475	24	.063/1.60	512562
5.374	4.114	40	.080/2.03	512501
5.374	4.114	40	.090/2.29	512509
5.374	4.114	40	.090/2.29	512510
5.374	4.114	40	.090/2.29	512516
5.374	4.018	46	.068/1.73	512821
5.375	4.125	24	.063/1.60	512557
5.375	4.280	49	.067/1.70	512828
5.376	4.323	45	.079/2.01	512462
5.376	4.323	45	.079/2.01	R600310
5.392	4.236	40	.073/1.85	512913
5.416	4.670	32	.062/1.57	512750
5.416	4.670	32	.055/1.40	512760
5.425	4.220	24	.062/1.57	512066
5.425	3.890	38	.067/1.70	512080
5.425	4.665	44	.067/1.70	512938
5.430	4.140	42	.067/1.70	512081
5.430	4.565	30	.067/1.70	512668
5.430	4.565	30	.071/1.80	512747
5.433	4.291	28	.072/1.83	512633
5.433	4.291	28	.085/2.16	512637
5.433	4.291	28	.072/1.83	512639
5.435	4.425	36	.059/1.50	512711
5.440	4.330	40	.060/1.52	512200
5.440	3.914	32	.071/1.80	512289
5.445	3.248	42	.070/1.78	512457
5.445	4.135	36	.062/1.57	512748
5.472	4.683	28	.062/1.57	512752

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
5.480	4.433	54	.062/1.57	512531
5.480	4.432	54	.048/1.22	512534
5.500	4.120	24	.064/1.63	512559
5.500	4.475	28	.082/2.08	512927
5.501	4.576	27/36	.098/2.49	512122
5.503	4.576	27/36	.082/2.08	512121
5.512	4.780	32	.063/1.60	512386
5.530	4.700	48	.060/1.52	512199
5.530	4.450	44	.080/2.03	512571
5.530	4.450	44	.080/2.03	R600040
5.550	4.655	47	.068/1.73	512827
5.580	4.605	36	.088/2.24	512941
5.585	2.500	22	.081/2.06	512173
5.585	4.348	33/44	.090/2.29	512872
5.585	4.348	33/44	.071/1.80	512962
5.585	4.348	33/44	.075/1.91	512963
5.585	4.348	33/44	.067/1.70	512965
5.585	4.348	33/44	.067/1.70	512976
5.585	4.355	44	.067/1.70	512986
5.585	4.348	33/44	.062/1.57	512993
5.590	2.500	19/22	.079/2.01	512241
5.590	2.500	19/22	.066/1.68	512245
5.593	4.621	30	.062/1.57	512273
5.599	4.459	51	.068/1.73	512826
5.600	4.158	51	.093/2.36	512169
5.610	4.450	36	.066/1.68	512837
5.610	4.450	36	.066/1.68	512838
5.619	4.535	30	.078/1.98	512112
5.620	4.445	30	.069/1.75	512419
5.620	4.445	30	.062/1.57	512781
5.620	4.331	24	.062/1.57	512880
5.620	4.457	48	.062/1.57	512882
5.630	4.570	58	.062/1.57	512926
5.655	4.750	48	.073/1.85	512524
5.660	4.335	30/36	.106/2.69	512055
5.660	4.335	30/36	.080/2.03	512056
5.670	4.569	30	.079/2.01	512720
5.675	4.475	24	.062/1.57	512058
5.700	4.550	48	.062/1.57	512852
5.701	4.533	24	.084/2.13	512182
5.705	3.043	24	.096/2.44	512390
5.709	4.497	30	.067/1.70	512097
5.710	4.760	24	.078/1.98	512865
5.722	4.812	60	.058/1.47	512090
5.725	4.812	55	.066/1.68	512567
5.733	4.472	32	.078/1.98	512364
5.737	4.700	12	.048/1.22	512535
5.737	4.792	50	.062/1.57	512789
5.737	4.792	50	.062/1.57	512792

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
5.740	4.670	57	.065/1.65	512219
5.748	4.780	40	.070/1.78	512209
5.748	4.521	63	.067/1.70	512217
5.748	4.521	63	.066/1.68	512220
5.750	4.752	20	.080/2.03	512703
5.750	4.752	20	.062/1.57	512705
5.750	4.752	20	.080/2.03	512706
5.750	4.752	20	.065/1.65	512707
5.750	4.752	20	.062/1.57	512710
5.750	4.752	20	.062/1.57	R600250
5.750	4.752	20	.080/2.03	R600255
5.754	4.505	52	.066/1.68	512221
5.776	5.010	36	.074/1.88	512296
5.780	4.645	30	.076/1.93	512246
5.780	4.960	30	.062/1.57	512884
5.780	4.960	30	.072/1.83	512885
5.780	4.960	30	.077/1.96	512886
5.783	4.880	62	.062/1.57	512970
5.783	4.880	62	.062/1.57	512974
5.785	4.610	39	.062/1.57	512159
5.790	4.970	56	.057/1.45	512089
5.790	4.342	36	.059/1.50	512164
5.790	4.970	56	.065/1.65	512563
5.790	4.970	56	.058/1.47	512568
5.793	4.618	36	.059/1.50	512166
5.800	4.730	30	.078/1.98	512731
5.800	4.730	30	.062/1.57	512738
5.800	4.730	30	.071/1.80	512739
5.800	4.680	28	.062/1.57	512777
5.814	4.656	54	.084/2.13	512183
5.820	3.874	48	.078/1.98	512141
5.829	4.577	30	.099/2.51	512117
5.830	4.575	30	.070/1.78	512084
5.830	4.632	36/48	.059/1.50	512978
5.830	4.632	36/48	.074/1.88	512979
5.838	5.000	36	.078/1.98	512732
5.838	5.000	36	.062/1.57	512733
5.838	5.000	36	.078/1.98	512736
5.838	5.000	36	.062/1.57	512737
5.845	4.720	30	.072/1.83	512587
5.856	4.778	27/36	.079/2.01	512148
5.856	4.779	27/36	.090/2.29	512151
5.870	4.810	30	.067/1.70	512103
5.870	5.005	61	.059/1.50	512815
5.871	4.812	30	.067/1.70	512098
5.876	5.166	34	.079/2.01	512727
5.880	5.040	8	.079/2.01	512724
5.880	4.852	30	.078/1.98	512734
5.880	4.565	38	.078/1.98	512758

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
5.880	4.975	30	.062/1.57	512952
5.895	4.328	42	.080/2.03	512152
5.895	4.328	42	.080/2.03	512352
5.895	4.328	42	.080/2.03	512355
5.895	4.328	42	.080/2.03	512458
5.895	4.328	42	.080/2.03	512614
5.895	5.190	30	.079/2.01	512744
5.910	4.673	20	.088/2.24	512250
5.910	4.673	20	.088/2.24	512251
5.910	4.673	20	.099/2.51	512512
5.910	4.673	20	.099/2.51	512520
5.910	4.673	20	.099/2.51	R600070
5.940	3.646	26	.080/2.03	512483
5.940	4.357	26	.080/2.03	512485
5.940	5.238	29/30	.077/1.96	512746
5.940	4.950	36	.072/1.83	512939
5.944	4.852	30	.062/1.57	512258
5.949	4.610	59	.065/1.65	512218
5.950	4.445	36	.070/1.78	512212
5.958	4.386	40	.066/1.68	512920
5.970	4.325	33/44	.096/2.44	512389
5.972	5.245	36	.057/1.45	512205
5.975	5.200	40	.057/1.45	512206
5.980	4.588	49	.067/1.70	512222
5.980	3.582	3	.062/1.57	512431
5.985	4.740	48	.072/1.83	512076
5.985	5.025	51	.072/1.83	512113
5.990	5.025	51	.072/1.83	512074
6.010	5.047	36	.065/1.65	512125
6.010	4.745	30	.082/2.08	512936
6.030	4.713	41	.080/2.03	512651
6.030	4.713	41	.080/2.03	512701
6.030	4.713	41	.070/1.78	512713
6.030	4.713	41	.070/1.78	R600280
6.035	5.200	44	.072/1.83	512906
6.056	4.961	36	.056/1.42	512281
6.062	4.945	50	.072/1.83	512521
6.063	4.996	32	.072/1.83	512631
6.063	4.996	31/32	.085/2.16	512632
6.063	4.996	32	.072/1.83	512634
6.063	4.996	31/32	.085/2.16	512635
6.066	4.582	30	.106/2.69	512105
6.075	4.496	36/48	.065/1.65	512234
6.080	5.360	42	.063/1.60	512384
6.080	4.432	54	.085/2.16	512530
6.080	4.432	54	.086/2.18	512532
6.080	4.432	54	.086/2.18	512709
6.085	5.075	20	.062/1.57	512771
6.085	5.075	20	.079/2.01	512774

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
6.094	5.089	32	.062/1.57	512785
6.094	5.089	32	.062/1.57	512790
6.095	4.870	20	.099/2.51	512118
6.100	4.449	24	.063/1.60	512257
6.100	5.025	36	.072/1.83	512588
6.100	4.960	30	.079/2.01	512778
6.140	5.260	32	.063/1.60	512665
6.140	4.965	64	.062/1.57	512772
6.140	4.965	64	.075/1.91	512773
6.140	5.120	33	.062/1.57	512775
6.150	5.245	3	.080/2.03	512975
6.155	5.220	30	.062/1.57	512192
6.160	4.935	40	.059/1.50	512675
6.178	5.258	30	.067/1.70	512099
6.180	4.970	56	.060/1.52	512091
6.180	4.970	56	.065/1.65	512564
6.180	4.970	56	.059/1.50	512575
6.181	5.209	36	.054/1.37	512282
6.184	5.363	54	.065/1.65	512538
6.184	5.363	54	.067/1.70	512548
6.185	4.810	30	.067/1.70	512100
6.185	4.810	30	.067/1.70	512101
6.185	5.322	40	.070/1.78	512914
6.185	5.322	40	.061/1.55	512922
6.200	5.295	54	.067/1.70	512082
6.200	4.715	31/34	.079/2.01	512240
6.200	4.715	31/34	.066/1.68	512244
6.230	5.297	40	.070/1.78	512194
6.250	5.245	24	.070/1.78	512160
6.250	5.245	24	.067/1.70	R600865
6.254	4.770	51	.080/2.03	512481
6.254	4.771	53	.080/2.03	512487
6.258	5.066	36	.062/1.57	512280
6.270	4.920	90/96	.077/1.96	512391
6.270	4.920	48	.077/1.96	512392
6.270	4.745	8	.062/1.57	512799
6.290	5.448	55	.065/1.65	512537
6.290	5.448	55	.067/1.70	512547
6.299	5.445	33	.068/1.73	512822
6.299	5.445	33	.066/1.68	512823
6.300	5.345	40	.062/1.57	512715
6.300	5.345	40	.077/1.96	512814
6.314	5.484	57	.059/1.50	512138
6.325	5.340	40	.072/1.83	512904
6.325	5.465	32/40	.072/1.83	512907
6.350	5.475	60	.070/1.78	512155
6.350	5.475	60	.067/1.70	R600840
6.365	4.922	90/96	.077/1.96	512047
6.365	4.922	90/96	.062/1.57	512361

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
6.365	4.922	57/60	.062/1.57	512454
6.365	4.922	90/96	.077/1.96	512762
6.365	4.922	90/96	.077/1.96	R600330
6.365	4.922	90/96	.062/1.57	R600335
6.365	4.922	90/96	.077/1.96	R600360
6.367	5.672	40	.058/1.47	512202
6.367	5.640	36	.058/1.47	512203
6.378	5.060	32	.078/1.98	512492
6.378	5.060	32	.078/1.98	512495
6.378	5.060	32	.089/2.26	512496
6.378	5.060	32	.058/1.47	512601
6.378	5.060	32	.051/1.30	512603
6.385	5.230	76	.078/1.98	512397
6.389	4.921	64	.062/1.57	512042
6.389	4.921	64	.077/1.96	512046
6.389	4.921	64	.077/1.96	512048
6.389	4.921	64	.077/1.96	512432
6.389	4.921	64	.077/1.96	R600340
6.389	4.921	64	.059/1.50	R600345
6.392	4.062	30	.067/1.70	512096
6.400	5.400	36	.098/2.49	512806
6.400	5.400	36	.099/2.51	512811
6.403	5.274	30	.063/1.60	512129
6.410	4.978	53	.080/2.03	512482
6.415	5.322	40	.072/1.83	512910
6.435	4.975	40	.072/1.83	512198
6.450	5.689	32	.072/1.83	512753
6.450	5.689	32	.062/1.57	512756
6.464	5.127	47	.062/1.57	512137
6.466	5.228	12	.062/1.57	512802
6.468	5.486	25	.088/2.24	512252
6.468	5.486	25	.088/2.24	512253
6.468	5.486	25	.098/2.49	512323
6.468	5.486	25	.099/2.51	512324
6.468	5.486	25	.099/2.51	512523
6.468	5.486	25	.099/2.51	R600010
6.468	5.486	25	.087/2.21	R600260
6.475	5.352	24	.070/1.78	512961
6.475	5.352	24	.079/2.01	512985
6.475	5.352	24	.079/2.01	512992
6.480	5.250	36	.085/2.16	512693
6.480	5.455	36	.082/2.08	512697
6.485	5.228	12	.062/1.57	512796
6.500	5.655	40	.081/2.06	512661
6.515	5.210	40	.063/1.60	512695
6.520	5.365	54	.065/1.65	512539
6.520	5.365	54	.067/1.70	512549
6.530	5.350	24	.080/2.03	512036
6.535	5.715	30	.070/1.78	512086

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
6.555	5.370	30	.062/1.57	512247
6.555	5.379	40	.070/1.78	512310
6.560	4.761	47	.080/2.03	512360
6.560	4.755	47	.080/2.03	512460
6.560	4.755	47	.072/1.83	512463
6.560	4.755	47	.080/2.03	512660
6.560	4.755	47	.090/2.29	R600090
6.560	4.755	47	.070/1.78	R600290
6.570	5.420	30	.062/1.57	512749
6.574	5.685	48	.071/1.80	512298
6.576	5.088	36	.068/1.73	512123
6.579	4.503	36	.070/1.78	512541
6.594	5.630	60	.077/1.96	512045
6.594	5.475	59	.078/1.98	512396
6.594	5.630	60	.077/1.96	R600430
6.595	5.708	40	.061/1.55	512154
6.595	5.698	36	.080/2.03	512585
6.595	5.610	50	.069/1.75	512729
6.595	5.708	40	.062/1.57	R600850
6.610	5.356	36	.074/1.88	512515
6.610	5.825	50	.079/2.01	512770
6.630	5.415	40	.062/1.57	512779
6.647	5.802	30	.063/1.60	512255
6.647	5.802	30	.085/2.16	512256
6.667	5.494	36	.079/2.01	512933
6.678	5.678	36	.065/1.65	512185
6.685	5.950	29/30	.062/1.57	512830
6.693	5.882	36	.061/1.55	512327
6.700	5.112	93	.062/1.57	512533
6.700	5.322	40	.071/1.80	512915
6.700	5.112	93	.062/1.57	R600870
6.703	5.085	62	.093/2.36	512581
6.703	5.085	62	.093/2.36	512582
6.703	5.085	62	.062/1.57	512591
6.703	5.085	62	.085/2.16	512592
6.703	5.085	62	.062/1.57	512679
6.703	5.445	36	.087/2.21	512803
6.703	5.085	62	.059/1.50	R600500
6.703	5.085	62	.084/2.13	R600502
6.703	5.085	62	.090/2.29	R600505
6.708	5.486	36	.080/2.03	512663
6.715	5.590	56	.058/1.47	512092
6.715	5.590	56	.065/1.65	512566
6.715	5.590	56	.060/1.52	512574
6.724	5.395	6	.062/1.57	512797
6.795	5.325	24	.076/1.93	512049
6.795	5.325	24	.078/1.98	R600400
6.798	5.468	72	.077/1.96	512350
6.798	5.468	72	.076/1.93	512393

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
6.798	5.468	72	.077/1.96	512450
6.799	4.862	6	.106/2.69	512108
6.810	5.790	36	.063/1.60	512550
6.810	5.526	48	.062/1.57	512605
6.810	6.050	50	.065/1.65	512669
6.812	5.920	30	.062/1.57	512163
6.812	5.671	53	.067/1.70	512987
6.815	5.765	30	.085/2.16	512692
6.815	5.765	30	.080/2.03	512698
6.845	5.625	36	.062/1.57	512340
6.846	5.394	32	.078/1.98	512491
6.865	6.005	30	.078/1.98	512586
6.874	5.438	12	.058/1.47	512602
6.874	5.438	12	.051/1.30	512604
6.885	6.008	45	.062/1.57	512843
6.887	5.758	70	.082/2.08	512943
6.887	5.758	70	.065/1.65	512944
6.890	5.446	36	.080/2.03	512572
6.890	5.446	36	.080/2.03	R600050
6.925	6.110	36	.062/1.57	512067
6.943	5.990	8	.079/2.01	512864
6.950	6.015	36	.067/1.70	512124
6.955	4.965	10	.116/2.95	512062
6.968	5.954	36	.071/1.80	512119
6.980	5.933	54	.062/1.57	512326
6.985	4.798	44	.064/1.63	512464
6.986	5.699	40	.072/1.83	512308
6.993	5.896	36	.081/2.06	512297
7.000	5.667	54	.062/1.57	512189
7.000	5.667	54	.062/1.57	R600925
7.005	5.965	3	.082/2.08	512971
7.021	5.830	38/40	.081//2.06	512181
7.025	5.835	30	.062/1.57	512421
7.025	5.845	30	.062/1.57	512857
7.030	5.715	30	.069/1.75	512085
7.030	5.715	30	.066/1.68	512087
7.030	5.715	30	.090/2.29	512114
7.030	5.715	30	.074/1.88	512116
7.030	6.250	40	.059/1.50	512761
7.049	5.364	36	.069/1.75	512168
7.065	6.145	36	.063/1.60	512552
7.071	6.252	36	.059/1.50	512131
7.071	5.712	36	.062/1.57	512270
7.071	4.557	44	.098/2.49	512623
7.073	6.077	40	.059/1.50	512134
7.073	5.630	60	.067/1.70	512224
7.073	5.630	60	.077/1.96	512225
7.073	5.630	60	.067/1.70	R600490
7.074	6.238	48	.062/1.57	512844

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
7.077	5.874	45	.062/1.57	512606
7.080	6.110	36	.063/1.60	512551
7.080	6.110	29/30	.063/1.60	512560
7.090	5.605	46	.063/1.60	512696
7.093	6.079	50	.061/1.55	512299
7.100	6.080	12	.080/2.03	512699
7.106	5.712	36	.066/1.68	512267
7.170	6.047	12	.079/2.01	512718
7.170	6.047	12	.079/2.01	512721
7.180	6.055	36	.072/1.83	512332
7.183	5.106	30	.099/2.51	512620
7.185	6.185	40	.106/2.69	512057
7.210	6.425	6	.062/1.57	512068
7.228	6.059	36	.062/1.57	512188
7.228	6.059	36	.062/1.57	R600915
7.230	5.875	40	.077/1.96	512262
7.230	5.875	40	.077/1.96	512263
7.230	6.177	75	.080/2.03	512946
7.240	6.060	36	.098/2.49	512328
7.240	6.425	40	.065/1.65	512565
7.244	5.773	40	.060/1.52	512309
7.245	5.400	20	.081/2.06	512948
7.300	6.052	60	.080/2.03	512461
7.300	6.052	60	.080/2.03	R600300
7.305	6.148	60	.067/1.70	512536
7.305	6.148	60	.067/1.70	512546
7.305	6.465	36	.063/1.60	512553
7.326	6.617	36	.059/1.50	512165
7.332	6.304	40	.072/1.83	512136
7.375	6.165	30	.082/2.08	512170
7.375	6.165	30	.062/1.57	512172
7.412	5.997	16	.090/2.29	512115
7.441	6.308	36	.071/1.80	512204
7.450	4.903	60	.099/2.51	512511
7.450	4.903	60	.098/2.49	512519
7.450	4.903	60	.096/2.44	R600075
7.485	6.325	3	.079/2.01	512972
7.492	6.365	36	.082/2.08	512583
7.496	6.360	24	.081/2.06	512329
7.510	5.870	24	.099/2.51	512643
7.518	5.290	54	.080/2.03	512484
7.518	5.290	54	.070/1.78	512486
7.533	5.725	46	.072/1.83	512135
7.540	6.305	32	.063/1.60	512666
7.586	6.221	28	.090/2.29	512288
7.641	6.517	48	.065/1.65	512128
7.651	6.366	36	.070/1.78	512187
7.651	6.366	36	.070/1.78	R600910
7.660	6.147	48	.078/1.98	512664

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #
7.715	6.800	58	.062/1.57	512854
7.720	6.715	32	.062/1.57	512848
7.720	6.800	58	.062/1.57	512853
7.721	6.529	36	.058/1.47	512126
7.721	6.482	30	.062/1.57	512127
7.755	5.845	30	.062/1.57	512422
7.790	5.630	60	.076/1.93	512050
7.793	5.911	50	.077/1.96	512043
7.793	5.911	50	.075/1.91	512053
7.793	5.911	50	.077/1.96	R600380
7.800	5.905	96	.078/1.98	512398
7.805	5.910	24	.078/1.98	512394
7.810	6.720	18	.082/2.08	512584
7.841	5.758	3 PAIR	.062/1.57	512800
7.874	6.366	36	.070/1.78	512184
7.874	6.366	36	.070/1.78	R600920
7.923	5.599	66	.078/1.98	512143
7.952	5.936	70	.066/1.68	512144
7.975	5.625	24	.086/2.18	512674
8.011	6.737	36	.074/1.88	512295
8.032	5.197	38	.126/3.20	512626
8.040	6.925	30	.063/1.60	512782
8.066	6.628	60	.078/1.98	512145
8.066	6.628	32	.078/1.98	512146
8.069	6.628	78	.078/1.98	512142
8.071	6.830	36	.058/1.47	512283
8.088	6.614	32	.062/1.57	512362
8.110	6.371	40	.091/2.31	512493
8.153	6.933	36	.055/1.40	512284
8.160	6.080	60	.099/2.51	512612
8.198	6.577	36	.062/1.57	512337
8.240	6.915	36	.062/1.57	512339
8.430	6.095	24	.088/2.24	512420
8.527	6.970	32	.084/2.13	512363
8.544	7.235	48	.062/1.57	512271
8.545	7.217	48	.063/1.60	512266
8.593	7.170	36	.073/1.85	512265
8.593	7.146	36	.057/1.45	512268
8.614	6.683	32	.065/1.65	512233
8.625	7.432	48	.062/1.57	512341
8.660	6.825	115	.099/2.51	512645
8.670	6.765	113/117	.099/2.51	512644
8.676	6.770	117	.071/1.80	512648
8.688	7.057	32	.080/2.03	512040
8.688	7.057	32	.080/2.03	512041
8.688	7.057	32	.077/1.96	512051
8.688	7.057	32	.077/1.96	R600420
8.690	7.195	64	.077/1.96	512044
8.690	7.195	64	.077/1.96	R600410

Allomatic Friction Dimensions

OD	ID	Teeth	Thickness	Part #